

PROFIT TECHNOLOGY

LEAD THE CHANGE

WITH 2823RT (6x4)



Gross Vehicle Weight - GVW

Vehicle Dimensions	
Wheel Base (mm)	4275
Cabin	Sleeper Cabin
Overall Length (mm)	7335
Overall Width (mm)	2490
Overall Height (mm) (CBC)	2960
Front Overhang (mm)	1485
Rear Overhang (mm)	900
Ground Clearance (mm)	247
Engine	
Engine Model	OM926
Maximum Power, kW	180kW @ 2200 rpm
Maximum Torque, Nm	850Nm @ 1200 -1600 rpm
No. of cylinders, cc	6, 7200
Emission Standard	Bharat Stage VI - OBD-2
Transmission	
Gear Box Model & Type	G85, 6F+1R, Mechanical, Synchromesh Gears
Clutch Type	Single Plate, Dry Type
Clutch Dia, Wear (mm)	395, 3.5
Power Take Off	Gearbox PTO Spline - Standard
Axle	
Front Axle	IF 7.0
Rear Axle	IRT390-11
Rear Axle Ratio	5.375
Chassis Frame & Suspension	
Frame Section (D X W X T) mm	$284 \times 70 \times 8$
Front Suspension	Parabolic
Rear Suspension	Balancer
Anti-roll Bar	Standard on front & first rear axle
Brakes	
Service Brake	Pneumatic, Foot Operated, Dual Line with ABS
Parking Brake	Pneumatically Operated Hand Control Valve
Front Brake Size (mm) & Type	Ø 410 drum
Rear Brake Size (mm) & Type	Ø 410 drum
Steering	
Steering Type	Hydraulic Power Assisted
Fuel & Electrical System	
Fuel Tank / Filling Capacity	330L / 310L
Adblue Tank / Filling Capacity	60L/51L
Battery Capacity	120Ah
Voltage	24V
Performance	
Maximum Gradeability %	21,20%
Maximum Geared Speed kmph	60 kmph
TCD	18.7 m
Tyres	
Pattern & Size	Radial Tyres - 295/90R20
Weight	

28000 kgs